



SUPERSOAK FORECOURT CLEANER

[Fast Acting, Heavy Duty Alkaline Soak Forecourt Cleaner]

INTRODUCTION

SUPERSOAK FORECOURT CLEANER is an exceptionally effective alkaline soak cleaner developed in America to clean oily greasy and dirty deposits from service station forecourts SUPERFAST. Cleaning time may be cut by as much as 50% and CLEANING POWER DOUBLES that of any conventional forecourt cleaner. SUPERSOAK is powerfully formulated to remove oily, greasy and carbonaceous soils, pigmented compounds, mild rust deposits and soft paint spills. A multi-component surfactant system provides increased wetting, detergency, emulsifying and soil penetration action and maintains a high level of activity for extraordinarily long periods. SUPERSOAK is safe on steel and stainless steel. It produces a slight tarnish on copper and brass,. However avoid contact with aluminium and zinc as concentrated solutions may cause etching.

ADVANTAGES

- Exceptionally fast cleaning reduces labour costs.
- Powerful cleaning action removes toughest soils resulting in a cleaner forecourt.
- Chealated for faster rinsing regardless of water hardness.
- High level of detergency ensures that soils stay in solution during disposal, i.e. will not redeposit oil and grease in drain ways.
- Economical - simple to operate, no expensive equipment required.

APPLICATION

Firstly choose a manageable area to clean then wet down surface to be cleaned using clean water. After making sure that adequate protective clothing is worn then lightly sprinkle wetted area with SUPERSOAK POWDER. Agitate well using a hard bristle broom and allow to stand for 10 to 15 minutes. Re-agitate with hard bristle broom and rinse off using clean water preferably under pressure if possible. Ensure that rinse water goes to drain away. If area to be cleaned is exceptionally dirty a longer contact time or a second application may be necessary. Please note that some forecourts are paved using a porous paving brick which acts like a sponge to absorb oil and diesel and as a result numerous applications may be necessary to completely emulsify all absorbed oil and grease and to float out the resultant emulsion. (NOTE: Porous paving bricks are not recommended for use in service station forecourts.)

CAUTION: KEEP CONTAINER SEALED WHEN NOT IN USE TO AVOID POWDER ABSORBING MOISTURE FROM THE ATMOSPHERE WHICH COULD CAUSE THE POWDER TO BECOME NON- FREE FLOWING

CAUTIONS

SUPERSOAK POWDER and solutions are alkaline and can cause burns. Exercise caution in its use. Wear Rubber gloves, safety goggles and Wellington boots. AVOID CONTACT WITH SKIN, EYES AND CLOTHING. Do not breathe dust or mist. In case of eye contact, flush well with large amounts of cold water and consult a Physician. If swallowed, do not induce vomiting and consult a Physician as a matter of urgency.

WARRANTY

We warrant our goods to conform to our standard specifications. This warranty is in lieu of any and all other warranties or guarantees. Our obligation hereunder for breach of such warranty is limited to either refund of the purchase price or replacement of said product as we may elect. We make no other warranties, express or implied, including those of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE.

We believe that the statements, technical information and recommendations contained herein are reliable, but are given without warranty or guarantee of any kind except as specified above. Beyond that specified above, we assume no responsibility for any loss, damage or expense, direct or consequential, arising out of the use of, or inability to use, our goods. Their quality and suitability for a particular purpose or use should be confirmed by the user's own tests.

STANDARD PACKAGES

1 Kg

5 Kg

25 Kg